

ЭКСПЕРТНОСТЬ

ПРОФЕССИОНАЛИЗМ

НАДЕЖНОСТЬ



кузбассэкотранс


НАДЁЖНЫЙ ПОСТАВЩИК КАЧЕСТВЕННЫХ ШИН

ПРОИЗВОДИТЕЛЯ LOADMAX

Рулевая шина



EP298++



- Adopted "Plus+" concept.
- Added more mileage.
 - widen tread width and revised land/sea ratio.
- Given more stability.
 - widen shoulder and center rib given more road holding.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
11R22.5	TL	16	146/143	M	1054	279	15.0	8.25	3000	2725	830
295/80R22.5	TL	18	152/149	L	1044	298	15.0	9.00	3550	3250	900
315/80R22.5	TL	20	157/154	L	1076	312	15.0	9.00	4125	3750	900

Ведущая шина

EP277



- Block tread design provide strong traction and braking power.
- Tough belt construction for smooth wear and longer mileage.
- Reinforced bead and body to ensure durability.



Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
315/80R22.5	TL	20	157/154	L	1076	312	22.0	9.00	4125	3750	900

Ведущая шина



EP296+



- Adopted plus+ concept.
- Added more mileage.
 - Widen tread width.
 - Increased road contact area.
- Increased gripping power.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
295/80R22.5	TL	18	152/149	L	1044	298	18.0	9.00	3550	3250	900
12R22.5	TL	18	152/149	L	1085	300	20.5	9.00	3550	3250	930

Универсальная шина для всех осей



EP268



- Shoulder lugs for more traction and center ribs are for stable handing.
- Tough belt for smooth wear and longer mileage.
- Special tread compound for high resistance tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
6.50R16LT	TT	12	110/105	L	750	185	10.5	5.50F	975	850	560
7.00R16LT	TT	14	118/114	L	775	200	12.0	5.50F	1320	1180	770
7.50R16LT	TT	14	122/118	K	805	215	13.0	6.00F	1500	1320	770
8.25R16LT	TT	16	128/124	K	855	235	14.5	6.50F	1800	1600	770
8.25R20	TT	16	139/137	K	974	236	15.0	6.5	2430	2300	930
9.00R20	TT	16	144/142	K	1019	259	15.5	7.0	2800	2650	900
10.00R20	TT	18	149/146	K	1054	278	16.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1085	293	17.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1125	315	17.5	8.5	3750	3450	830
12.00R24	TT	20	160/157	K	1226	315	17.5	8.5	4500	4125	900
11R22.5	TL	16	146/143	M	1054	279	17.5	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1085	300	17.0	9.00	3550	3250	930
13R22.5	TL	18	154/151	L	1136	320	18.0	9.75	3750	3450	830
315/80R22.5	TL	20	157/154	L	1076	312	18.0	9.00	4125	3750	900

Внедорожная шина

Product characteristics

- ▶ Applicable for driving wheels. Suitable for short distance with low speed on mining and bad roads.
- ▶ Excellent pattern design offers good pulling force.
Special tread compound offers excellent cut resistance.
- ▶ Reinforced bead area reduces the deformation of this area, provides excellent load capacity than normal tyres.



Size	Service Index	LR/PR	Tread Depth (mm)	Standard Rim	O.D(mm)	Section Width (mm)	Max. Load Capacity(kg)		Inflation Pressure(kpa)	
							Single	Dual	Single	Dual
11R22.5	148/145L	16PR	24.0	8.25	1050	279	3150	2900	850	850
11R24.5	149/146L	16PR	24.0	8.25	1104	279	3250	3000	830	830
12R22.5	152/149L	18PR	24.0	9.00	1085	300	3550	3250	930	930
12.00R20	156/153F	20PR	24.0	8.50	1136	315	4000	3650	900	900
12.00R20 HD	158/155F	22PR	24.0	8.50	1136	315	4250	3875	970	970
12.00R24	160/157B	L/20	30.0	8.50	1226	315	4500	4125	900	900
12.00R24	168/165B	L/24	30.0	8.50	1226	315	5600	5150	930	930
295/80R22.5	152/149F	J/18	21.0	9.00	1044	298	3550	3250	900	900
315/80R22.5	167/164D	M/22	24.0	9.00	1076	312	5450	5000	950	950



**СВЯЖИТЕСЬ С ВАШИМ
МЕНЕДЖЕРОМ**



Телефон

+7 (903) 909-88-41

Почта

info@k-e-t.ru

Сайт

k-e-t.ru

Адрес

Кемеровская обл., г. Новокузнецк, Курако, д. 49А